



## **BROMINE PROGRAM FOR SPAS**

### **EVERY TIME YOU USE YOUR SPA**

- You need to maintain the proper amount of Bromine in your spa at all times. This level should be from 2-5 ppm. Add enough bromine tablets to floater to last for a week. Fill as necessary. You may also choose to add granular bromine when needed.

### **ONCE PER WEEK**

- Check PH & Alkalinity with test strip. Adjust up or down as necessary. Some people may find that you only need to adjust one and not the other. You can use Spa Up or Spa down to adjust for both. Otherwise, you can use PH Increaser or Decreaser to adjust PH individually. If you need to raise alkalinity, then use an alkalinity increaser. Low or High levels of ph and alkalinity can be corrosive and may shorten the life of your equipment as well as make it difficult to keep your water clear.
- You also need to check your calcium hardness levels with your test strips to prevent calcium build up in the spa. Low CH can also attribute to cloudy or foamy water. To raise calcium hardness, you either Calcium Hardness Increaser, or Calcium Booster.
- Once PH & Alkalinity are in ideal range, we recommend that you shock your spa to oxidize contaminates that can build up in the water. You can do this with a spa shock/oxidizer or Renu. If your spa is less than 300 gallons, use 2 oz. More than 300 gallons use 4 oz. Run jets **with cover off** for 30-45 minutes.
- We also recommend that you add Spa Defender or Stain & Scale Control according to directions to prevent calcium buildup in plumbing and equipment.

### **ONCE PER MONTH**

- Shut off power to spa and remove filters.
- Spray on Filter Clean. Let cleaner penetrate for 3-6 minutes. If you use a soaking filter cleaner, follow directions on back of bottle for this procedure.
- After filters have been sprayed or soaked, rinse thoroughly with high pressure, and rotate filters to prolong filter life.
- Make sure filters are secure and power spa up.
- We recommend that you condition your cover monthly to protect the vinyl encasement. Clean cover with mild soap and water. Then apply 303 Protectant to save your cover from harmful UV rays, and prolong covers life.

### **ONCE EVERY 4 MONTHS**

- We recommend that you drain, clean, and refill spa 2-3 times per year. Once you refill your spa with fresh water, we also recommend that you add Spa Metal Gon or Stain & Scale to prevent mineral buildup in plumbing and equipment.

**\*\*\*Filters need to be replaced within 1 to 2 years depending on usage of spa.**